

Driving Floor Scrubber DQX6



Advantages

- Large area of the sewage tank cover, easy to clean and maintain, to avoid the breeding of bacteria.
- Ultra-quiet design, say goodbye to harsh noises.
- Backward squeegee automatically rises, to prevent damage of the squeegee.
- Strong passability, suitable for narrow aisles.
- Using imported controller, the product is stable and reliable.

Advantages



Cautions

- 1.No-load climbing capacity is 15%,please empty the water tank when climbing, climbing of large slopes frequently may cause damage to the rear axle.
- 2.Please turn off the brushing function before raising the brush plate, otherwise, the brush plate is easy to fall.
- 3.Pay attention to raise the brush disc when passing the speed belt, reduce speed properly

Specifications

Model	DQX6(Double brush disk)	Unit
Dimension(l*h*w)	1280*700*1070	mm
Packaging dimension(l*h*w)	1420*780*1250	mm
Cleaning Width	660	mm
Cleaning efficiency	3800	m ² /H
Weight (with battery)	246	kg
Power	1710	W
Drive axle power	500	W
Brush motor power	2*380	W
Suction motor power	450	W
Working voltage	24	V
Running speed	5.6	Km/h
Backward speed	2.7	Km/h
Clean water tank capacity	70	L
Sewage tank capacity	75	L
Suction scraper width	820	mm
Sound	68	dB
Brush pressure	35	kg
Working time	≈4	H
Climbing ability (no load)	≤15	%
Minimum turning radius	1200	mm
Lead-acid battery (standard)	24V150AH	-
Charging time	8~10	H
Lithium battery (optional)	25.6V150AH	-