



Advantages











Cautions

- 1. No load climbing capacity is 20%, please empty the water when climbing.
- 2. Prompt to charge in time when the battery is low, do not switch on and off repeatedly.
- 3. Pay attention to raise the brush disc when passing the speed belt, reduce speed properly.

ecifications			
Model	DQX86A (front drive)	DQX86B (rear drive)	Uni
Boundary dimension(l*h*w)	1600*950*1375	1600*950*1375	mn
Packaging dimension(l*h*w)	1730*1020*1420	1730*1020*1420	mn
Cleaning width	860	860	mn
Cleaning efficiency	5000	5000	m ² /
Weight (with battery)	370	370	kg
Power	2600	2600	W
Drive axle power	900	900	W
Brush motor power	2*550	2*550	W
Suction motor power	550	550	W
Working voltage	24	24	V
Running speed	5.6	5.6	Km/
Backward speed	3.5	3.5	Km/
Clean water tank capacity	130	130	L
Sewage tank capacity	150	150	L
Suction scraper width	1120	1120	mn
Sound	65	65	dB
Brush pressure	44	44	kg
Working time	≈5	≈5	Н
Climbing ability (no load)	≤17	≤20	%
Minimum turning radius	850	1400	mn
Lead-acid battery	24V225AH	24V225AH	-
Charging time	8~10	8~10	Н
Lithium battery (optional)	25.6V200AH	25.6V200AH	_