



| | | | |
|-------------------|--|-------------|---------|
| Series | 5000 | Warranty | 5 Years |
| Volts | 4 | BCI | SPEC |
| Cells | 2 | Plates/Cell | 21 |
| Terminal Type | Flag | | |
| Included Hardware | S/S Hex Cap Screw, Nut, Lock & Flat Washer | | |
| Size & Thread | 5/16"-18 | | |
| Cables | 19" 4/0 interconnect cables *RE incl. | | |

Charge

| | |
|----------------------|---------------------------------|
| Charge Voltage Range | 2.45-2.5 V/cell @ 25°C (77°F) |
| Float Voltage Range | 2.25 V/cell @ 25°C (77°F) |
| Self-Discharge Rate | 5%-10% per month at 25°C (77°F) |

Capacity

| | | | | |
|------------------------------------|--------------|-------------|------------|-------------|
| Cold Crank Amps (CCA) 0°F / -18°C | 2754 | | | |
| Marine Crank Amps (MCA) 32°F / 0°C | 3443 | | | |
| Reserve Capacity (RC @ 25A) | 2756 Minutes | | | |
| Reserve Capacity (RC @ 75A) | 919 Minutes | | | |
| Capacity Affect by Temperature | 40°C (104°F) | 25°C (77°F) | 0°C (32°F) | -15°C (5°F) |
| | 105% | 100% | 75% | 50% |

| Hour Rate | Capacity / AMP Hour | Current / AMPS |
|-----------------|---------------------|-----------------|
| @ 100 Hour Rate | 1481 AH | 14.81 A |
| @ 72 Hour Rate | 1401 AH | 19.45 A |
| @ 50 Hour Rate | 1326 AH | 26.52 A |
| @ 20 Hour Rate | 1148 AH | 57.41 A |
| @ 15 Hour Rate | 1068 AH | 71.19 A |
| @ 10 Hour Rate | 1022 AH | 102.19 A |
| @ 8 Hour Rate | 987 AH | 123.43 A |
| @ 5 Hour Rate | 919 AH | 183.71 A |
| @ 1 Hour Rate | 517 AH | 516.67 A |

Ampere hour capacity ratings based on specific gravity of 1.280 at 27°C (80°F). Reduce capacities 5% for specific gravity of 1.265 and 10% for 1.250.

Specifications




| | | |
|-------------------|---------|---------|
| Weight | 121 kg | 267 lbs |
| Length | 40 cm | 15.75" |
| Width | 23.8 cm | 9.38" |
| Height Inc. Term. | 62.9 cm | 24.75" |

Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process & battery components.

| | | |
|---------------------|---|-------|
| Electrolyte Reserve | 95 mm | 3.75" |
| Container (Inner) | Polypropylene | |
| Cover (Inner) | Polypropylene - heat sealed to inner container | |
| Container (Outer) | High Density Polyethylene | |
| Cover (Outer) | High Density Polyethylene snap fit to outer container | |
| Handles | Molded | |

Cycle Life vs. Depth of Discharge



Voltage vs. Depth of Discharge

| DISCHARGE | 0% | 25% | 50% | 75% | 100% |
|---------------|--------|--------|--------|--------|--------|
| 20 HR AH RATE | 2.10 V | 2.05 V | 2.02 V | 1.96 V | 1.75 V |
| 6 HR AH RATE | 2.10 V | 2.04 V | 2.00 V | 1.95 V | 1.75 V |
| 1 HR AH RATE | 2.10 V | 2.03 V | 1.99 V | 1.94 V | 1.75 V |

Detailed Illustration

